

Claims

1. An anchoring apparatus for attachment to a safety device and to an anchor bolt, comprising:

a flexible connector member having,

an end, and

a loop defining an aperture configured to receive and retain the anchor

bolt, the loop configured with a twist; and

a fastener disposed to secure the end to the connector member and retain the twist

in the loop.

2. The anchoring apparatus of claim 1 wherein the connecting member comprises a fabric material.

3. The anchoring apparatus of claim 1 wherein the fastener comprises stitches.

4. The anchoring apparatus of claim 1 wherein the loop is configured with a plurality of twists, the fastener disposed to secure the end and retain the twists in the loop.

1 5. A method for making an anchoring apparatus for attachment to a safety device
2 and to an anchor bolt, the method comprising:
3 providing a flexible connector member having an end;
4 forming a loop in the connector member;
5 forming a twist in the loop; and
6 securing the end to the connector member to retain the twist in the loop and to
7 define an aperture to receive and retain the anchor bolt.

8
9 6. The method for making an anchoring apparatus of claim 5, further comprising
10 forming a plurality of twists in the loop, and wherein the step of securing the end further
11 includes retaining the twists in the loop.

12
13 7. The method for making an anchoring apparatus of claim 5, wherein the
14 connector member comprises a fabric material.

15
16 8. The method for making an anchoring apparatus of claim 5, wherein securing
17 the end comprises stitching the end to the connector member.

18
19
20
21

- 1 9. An anchoring apparatus for attachment to a safety device and to an anchor bolt,
2 comprising:
3 a flexible connector member having,
4 an end,
5 a loop defining an aperture configured to receive and retain the anchor
6 bolt, and
7 a knot disposed proximate to the loop and the end, the knot further
8 defining the aperture; and
9 a fastener disposed to secure the end to the connector member.
10
11 10. The anchoring apparatus of claim 9 wherein the connecting member
12 comprises a fabric material.
13
14 11. The anchoring apparatus of claim 9 wherein the fastener comprises stitches.
15
16 12. The anchoring apparatus of claim 9 wherein the loop is configured with a
17 twist, the fastener disposed to retain the twist in the loop.
18
19 13. The anchoring apparatus of claim 9 wherein the fastener is disposed to retain
20 the position of the knot.
21

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21

14. The anchoring apparatus of claim 9 wherein the knot is configured as a slip
knot.

- 1 15. A method for making an anchoring apparatus for attachment to a safety
2 device and to an anchor bolt, the method comprising:
3 providing a flexible connector member having an end;
4 forming a loop in the connector member, the loop defining an aperture to receive
5 and retain the anchor bolt;
6 forming a knot in the connector member proximate to the loop, the knot further
7 defining the aperture; and
8 securing the end to the connector member to retain the position of the loop.
9
10 16. The method for making an anchoring apparatus of claim 15, further
11 comprising forming a twist in the loop, and wherein the step of securing the end further
12 includes retaining the twist in the loop.
13
14 17. The method for making an anchoring apparatus of claim 15, wherein the
15 connector member comprises a fabric material.
16
17 18. The method for making an anchoring apparatus of claim 15, wherein securing
18 the end comprises stitching the end to the connector member.
19
20
21